

DEMISTER PAD INSTALLATION INSTRUCTIONS

- Permanently sealed Operates by 230 volt power supply
- Wires into existing or dedicated lighting circuits
- Suitable for indoor use only $t_a=25^{\circ}\text{C}$

IMPORTANT

- Never leave anything across the mirror surface which will prevent heat dissipating fully. This may cause the Demister Pad to overheat the mirror.
- Never cut the Demister Pad as this will damage the insulation rendering the pad electrically unsafe. Note the label on the Demister Pad.
- The electrical connection for your Demister Pad should be carried out by a Registered Electrician.

PLEASE READ FULLY BEFORE INSTALLING :

- ① Mark the exact location on the back of the mirror where you require the Demister Pad to be positioned.
- ② Prior to applying the Demister Pad to the back of the mirror, ensure the mirror back is absolutely clean and free of dust.
- ③ Remove the self adhesive tape protective strips from the Demister Pad.
- ④ Locating your marks on the mirror back, position one edge of the Demister Pad and gently lay the pad onto the mirror back, ensuring the self adhesive tape strips have bonded.
- ⑤ Under no circumstances remove or reposition the pad as damage to the pad may result.
- ⑥ Where necessary, cut out an access in the wall to accommodate connection to a light fitting or connection to a dedicated light switch. Then affix the mirror to the wall using the chrome clips. Please consult with your electrician before proceeding with installation.

ST MICHEL INDUSTRIES LIMITED OR OUR DISTRIBUTOR PARTNERS AND SUPPLIERS CANNOT BE HELD RESPONSIBLE FOR DAMAGE CAUSED BY IMPROPER INSTALLATION.

05/23